



Vessel : MATILDA ex SIBOELF

Owner : Matilda Shipping Ltd.

Description :

**M/OBO MATILDA**

---

LIB FLAG GL ST DOUBLE-SKINNED OBO

BLT 1993 B&W, COPENHAGEN

74,868 MTS DWAT ON 14.480 M SSW DRAFT AS TANKER

72,329 MTS DWAT ON 14.112 M SSW DRAFT AS BULKER

CONSTANTS ABT 600 TS INCL FW EXCL BUNKERS / SLOPS

69 TPC SUMMER DRAFT

GRT/NRT: 41.189/25.692

228.60 M LOA, 32.272 M BEAM

IGS/COW/SBT FITTED

PARTLY COATED IN CARGO TANKS

HEAT EXCHANGER ON DECK

DISTANCE KTM 47 M

DISTANCE BCM 109.10 M

OIL CUBIC CAPACITY 98 PCT OF CARGOTANKS 81.930 CBM

OIL CUBIC CAPACITY 98 PCT OF SLOPTANKS 928 CBM

VESSEL FITTED WITH PROGRAMMABLE COW MACHINES

PANAMA NRT: 35.806

VSSL FITTED WITH VAPOUR LOCK/RECOVERY SYSTEM

**SPEED/CONS:**

SPEED AND CONSUMPTION WP UP TO AND INCL. BF 4 DSS 3

BALLAST ABT 14,0 KN ON ABT 34 MTS IFO RMG380 PD PLUS 0.1 MT MGO PD

LADEN ABT 13.2 KN ON ABT 34 MTS IFO RMG380 PD PLUS 0.1 MT MGO PD

IDLE IN PORT: ABT 3 MTS IFO RMG380 PLUS 0.5 MT MGO PD

HEATING: CONSUMPTION PER DAY ABT 10 MTNS IFO DEPENDING ON AMBIENT + SEAWATER

TEMPERATURE

PUMPING: ABT 15 TNS IFO / 24 HRS

INERTING: APPX 18 MT MGO PER 24 HRS

CLEANING: ABT 50 MT IFO + 10 MT MGO FOR CLEANING FM DPP TO DPP OR DPP TO COAL /

IRON ORE ALWAYS DEPENDING ON CARGO HISTORY AND SPECS OF LAST CARGO

SPECS: IFO RMG380 MAX AL + SI 50 PPM / MGO DMA MAX 0,2 PCT SULPHUR AS PER ISO

8217 3RD EDITION 2005

IN SECA AREAS VESSEL TO BURN IFO WITH MAX 1.5 PCT SULPHUR BUNKER

DELIVERY TO BE CONFORMING TO REGULATIONS 14 & 18 OF ANNEX VI OF MARPOL 73/78

VSL MIGHT BURN MGO WHEN MANOUVERING IN NARROW WATERS (APPROX 2 MTS PER HOUR)  
(ALL DETS ABOUT)

9 HOLDS / 9 HATCHES

HATCH 1: 9.00 X 11.20 M / HATCHES 2 - 9: 13.50 X 16.00 M

TANK SEGREGATIONS:

THREE GRADES FULL LINE SEGREGATION AS FOLLOWS:

AAA) CARGO TANKS 1+5+8

BBB) CARGO TANKS 2+6+7

CCC) CARGO TANKS 3+4+9

-----

**CARGO HOLDS/TANK CAPACITIES**

CBMS BBLs CBMS GRAIN GRAIN

100 % 100 % 98 % CBMS CBFT

---

HOLD 1	5943	37380	5824	5926	209.270
HOLD 2	9193	57822	9009	9162	323.547
HOLD 3	9782	61527	9587	9752	344.384
HOLD 4	9796	61615	9600	9765	344.841
HOLD 5	9796	61615	9600	9765	344.841
HOLD 6	9796	61615	9600	9765	344.841
HOLD 7	9796	61615	9600	9765	344.841
HOLD 8	9796	61615	9600	9765	344.841
HOLD 9	9705	61043	9510	9671	341.522

---

TOTAL 83601 525847 81930 83336 2,942.927

SLOP S 474 2981 464

SLOP P 474 2981 464

---

TOTAL 84549 531809 82858